


FORM PTO-1199 (REV. 12-97)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER 5418	
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371					
INTERNATIONAL APPLICATION NO. PCT/FR99/01904		INTERNATIONAL FILING DATE 2 August 1999		U.S. APPLICATION NO. (if known, see 37 CFR 1.5) 09/744946	
				PRIORITY DATE CLAIMED 4 August 1998	
TITLE OF INVENTION FILTERING ELEMENT MADE OF ABSORBENT PAPER MATERIAL IN THE FORM OF A TUBULAR CYLINDER					
APPLICANT(S) FOR DO/EO/US Yves MALECOT and Joel HUNGLER					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
<p>1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.</p> <p>2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.</p> <p>3. <input checked="" type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 36.</p> <p>4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.</p> <p>5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2))</p> <p style="margin-left: 20px;">a. <input checked="" type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau).</p> <p style="margin-left: 20px;">b. <input type="checkbox"/> has been transmitted by the International Bureau.</p> <p style="margin-left: 20px;">c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US).</p> <p>6. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)).</p> <p>7. <input type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))</p> <p style="margin-left: 20px;">a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau).</p> <p style="margin-left: 20px;">b. <input type="checkbox"/> have been transmitted by the International Bureau.</p> <p style="margin-left: 20px;">c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired.</p> <p style="margin-left: 20px;">d. <input type="checkbox"/> have not been made and will not be made.</p> <p>8. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).</p> <p>9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). (unexecuted)</p> <p>10. <input type="checkbox"/> A translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).</p> <p>Items 11. to 16. below concern document(s) or information included:</p> <p>11. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98.</p> <p>12. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.</p> <p>13. <input type="checkbox"/> A FIRST preliminary amendment.</p> <p style="margin-left: 20px;"><input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment.</p> <p>14. <input type="checkbox"/> A substitute specification.</p> <p>15. <input type="checkbox"/> A change of power of attorney and/or address letter.</p> <p>16. <input checked="" type="checkbox"/> Other items or information:</p>					



U.S. APPLICATION NO. 09/744946		INTERNATIONAL APPLICATION NO. PCT/FR99/01904		ATTORNEY'S DOCKET NUMBER 5418	
---------------------------------------	--	---	--	----------------------------------	--


17. <input checked="" type="checkbox"/> The following fees are submitted:				CALCULATIONS PTO USE ONLY	
BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)):					
Search Report has been prepared by the EPO or JPO..... \$ 860.00					
International preliminary examination fee paid to USPTO (37 CFR 1.482) \$ 690.00					
No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)) \$ 710.00					
Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$1000.00					
International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4) \$ 100.00					
ENTER APPROPRIATE BASIC FEE AMOUNT =				\$	860.00
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input checked="" type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$	130.00
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE.	\$	
Total claims	15 - 20 =	0	x \$ 18.00	\$	0
Independent claims	1 - 3 =	0	x \$ 80.00	\$	0
MULTIPLE DEPENDENT CLAIM(S) (if applicable)				\$270.00	\$ 270.00
TOTAL OF ABOVE CALCULATIONS =				\$	1260.00
Reduction of 1/2 for filing by small entity, if applicable. A Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28).				+	\$ 0
SUBTOTAL =				\$	1260.00
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$	0
TOTAL NATIONAL FEE =				\$	1260.00
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +				\$	0
TOTAL FEES ENCLOSED =				\$	1260.00
				Amount to be refunded:	\$
				charged:	\$

a. ☒ A check in the amount of \$ 1260.00 to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 02-3690. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO: Breiner & Breiner 115 North Henry Street P.O. Box 19290 Alexandria, VA 22320-0290 Date: January 31, 2001	 SIGNATURE Mary J. Breiner NAME 33,161 REGISTRATION NUMBER
---	---

2/PATS

09/744946
526 Rec'd PCT/PTO 31 JAN 2001

PCT/FR99/01904

FILTERING ELEMENT MADE OF AN ABSORBENT PAPER MATERIAL
IN THE FORM OF A TUBULAR CYLINDER

The present invention relates to a filter element.

More specifically, the present invention relates to a filter element for use in filtering a fluid and designed for use within a filtration system including a cylindrical case, the filter element being made of an absorbent paper material in the form of a sheet configured to subtend a tubular cylinder and being arranged within the case to partition an outer radial portion from an inner radial portion, the fluid moving across the filter element in a generally centripetal direction.

Such a filter element, illustratively, is described in French Patent Document 2,624,397 A.

This Document describes a filter element used in particular for ultrafine filtering lubrication oil of an automobile's internal combustion engine.

Such filter elements are designed to be housed in a case of a filter system which is entered by a fluid at its peripheral zone and which fluid leaves, following filtration through a central zone.

In French Patent Document 2,624,397 A, the filter element is made of a paper strip which is wound around a cardboard core, the core being perforated by an array of holes to pass the fluid. The oil must cross in one way or another the cardboard core to arrive at the outlet of the case.

Such filter elements offer many advantages. They are manufactured using techniques widely used, in particular, in making rolls of toilet paper or paper towels. Making the filter element in the form of a wound strip of paper is especially advantageous because of the ease in winding such a strip and the filtering quality is especially high and, moreover, can be customized as a function of the particular material being used and of its winding density.

Nevertheless, the filter element described in French Patent Document 2,624,397 A incurs a serious drawback by the presence of the cardboard core. It has been observed that this cardboard core entails a high pressure drop when the fluid moves through the filter element, in particular as regards such fluids as high viscosity oils.

It must be borne in mind that the cross-section allowing the fluid to flow through the filter is limited to the sum of the cross-sections of each fluid transmitting perforation in the cardboard core. However, in the device of the Patent Document, the transmitting cumulative cross-section is only a few percent of the total surface of the inner cylindrical surface of the wound paper.

Moreover, the perforations are relatively far from each other, and are relatively few, and as a result favored fluid transmission zones will be created, in particular and obviously near these perforations. Because some zones filter more oil than others, these zones will collect more particles

than others in the filter element, and hence they will clog earlier.

When the favored fluid transmission zones become clogged, the filtration quality drops significantly, with an accompanying increase in the pressure drop across the filter element.

Consequently, a filter element fitted with a perforated central core often must be replaced prematurely without the global volume of the filter element having attained a clogging level that would justify such a replacement.

Therefore, it is an object of the present invention to propose a novel filter element which on one hand allows significant reduction of the pressure drop across the filter element and on the other hand allows increase in the filter element's service life by homogeneously exploiting its full volume.

Accordingly, the invention proposes a filter element of the above described kind which is characterized by the absence of a central core in the filter element.

In other features of the invention:

- The mean inside diameter of the tubular cylinder is larger than $1/20^{\text{th}}$ its mean outside diameter,
- The mean inside diameter of the tubular cylinder is larger than $1/4^{\text{th}}$ its mean outside diameter,
- The mean inside diameter of the tubular cylinder is between $1/3$ and $1/2$ its mean outside diameter,

-- The mean inside diameter of the tubular cylinder is larger than 25 mm,

-- The inside wall of the tubular cylinder is conical or cylindrical and its cross-section is circular, polygonal or other,

-- On its surface, the cylindrical filter element is fitted with at least one polarizing positioning means,

-- The filter element has a strip of absorbing paper in the form of a single, continuous sheet wound into a tubular cylinder,

-- The filter element has a series of interlacing absorbent paper sheets constituting a tubular cylinder,

-- The sheet includes several plies,

-- The absorbent paper product is made of cellulose cotton,

-- It is designed to be used in a fluid filtering system, such as an oil filter of an automotive vehicle.

Other features and advantages of the invention are elucidated in the comprehensive discussion below and in relation to the attached drawings.

Figure 1 is an axial and schematic section of a filter system fitted with a filter element of the present invention, and

Figure 2 is a schematic cross-section in the plane of line 2-2 of Figure 1.

Figures 1 and 2 show a fluid filter system 10 substantially including a case 12 and a filter element 14. The case 12 is fitted with a cylindrical side wall 16 forming a body of revolution about the axis A1 and it is closed at its two axial ends by two lower and upper transverse lids 18 and 20. The lids 18, 20 are affixed to the axial ends of the side wall 16, for example by a screw connection or any other conventional means.

The casing 12 includes an intake 22 radially issuing into the side wall 16 so that a fluid may enter the inside of the case 12. The lower lid 18 is fitted at its center with an axially pointing orifice 24 constituting an outlet for the fluid after it has been filtered so that it can leave the case 12.

In the illustrated embodiment, the filter element 14 is a strip of paper, for example made of cellulose cotton, the strip being cylindrically wound about the axis A1 so as to substantially constitute a body of revolution about this axis, and, in the manner of the present invention, the cylindrical winding is devoid of any central core, as a result of which the inside wall of the filter element is constituted by the innermost turns of the wound paper.

The illustrated filter element therefore can be manufactured in the manner disclosed in the French Patent Document 2,544,799 A which is explicitly referred to herewith for all details relating to the manufacture of this filter

element. In summary, however, this procedure involves winding the paper strip around a conical or cylindrical bar of which the cross-section is circular, polygonal or other, or at least the cross-sections of the bar exhibit edges which run approximately parallel to the winding axis or subtend a simple or complex helix around the axis, the paper being folded at these edges. A compression roller is applied against the outside of the winding in progress and allows especially compact winding, and, when this winding bar exhibits edges in its cross-section, the compression roller neatly folds the paper where it makes contact with the edges.

In a simple embodiment of the invention, the winding bar exhibits the cross-section of a cylinder having a polygonal, for example a hexagonal, base.

The above illustrative embodiment is one of many. The invention includes winding bars of any other tubular shape, for example conical or cylindrical, and exhibits a circular or other cross-section.

Once winding has been terminated, the winding bar is retracted from the winding center, whereby the inside wall of the winding then exhibits a contour substantially as shown in Figure 2, wherein this inside wall is constituted of convex surface segments joined by turning points having the folding marks imparted by the edges of the winding bar.

On account of this contour and on account of these turning points, the inner winding turns are prevented from

unraveling inward, so that, even when unconstrained, the filter element retains its shape. The inside wall, of which the cross-section is defined by the winding bar, moreover may be reinforced in the manner described below.

As shown in Figure 1, the filter element 14 is configured in the case 12 in a manner that its two axial ends axially rest one against the lower lid 18 and the other against the upper lid 20, whereby, inside case 12, the filter element 14 defines two zones, namely a peripheral, outer zone 26 and a radial, inner zone 30, the zone 30 being radially bounded outward by the inside wall of the filter element's winding.

Accordingly, the fluid entering the case through the intake 22 reaches the inside of the external, peripheral zone 26. The outlet 24 issues into the inner, radial portion 30. Therefore, in order to exit the case 12, the fluid that has entered it perforce must cross the filter elements in substantially radially inward manner.

When manufacturing the filter element by the procedure disclosed in French Patent Document 2,554,799 A, windings having a mean inside diameter of about 25 to 40 mm may be made, that is, a diameter which is substantially equal to that of the windings made on a core.

Advantageously, the mean inside diameter of the filter element's winding is larger than $1/20^{\text{th}}$ the outside diameter of the winding, and preferably this mean inside diameter greater than $1/4^{\text{th}}$ the outside diameter of the winding, and most

preferably this mean inside diameter is between $1/3$ and $1/2$ the winding's outside diameter.

In fact, the inside diameter must be large enough to preclude the inside surface from being too small, there being danger that the inside radial part 30 will exhibit insufficient cross-section for adequate fluid flow and on the other hand there being danger that a small surface of the winding's inside wall entails a strong fluid pressure gradient near the inner turns of the windings.

In fact, fluid flow taking place radially inward, the flow per unit area increases when approaching the axis of the winding and hence the surface of the cylindrical surface at a given radius will decrease.

If the winding's inside diameter is too small, the core-less filter element will entail the same drawbacks regarding pressure drops as a filter element fitted with a perforated cardboard core.

The product made by the procedure described in French Patent Document 2,554,799 exhibits an inner wall having a polygonal cross-section whereby the filter element can be advantageously locked in place in a case without danger of its rotating inside it and in this manner assures simple affixation of this element. As shown in the Figures, this securing feature is easily implemented by centering the filter element in the case. Illustratively, these filtering elements may be in the form of centering stubs 32 which project from

the inside faces of the lids 18, 20 and which run axially within the inside radial portion 30 of the filter element while cooperating with the element's inside wall by means of their slightly conical side walls.

The cross-section of the inside wall is defined by the winding bar and this wall also may be reinforced to totally preclude any warping by application of water or a solution containing an adhesive or any other additive at least at the beginning of winding the paper strip in the manner discussed in French Patent Document 2,554,799. The inside wall may be further reinforced by knurling or any other method linking the turns. In this manner, the inside wall of the filter element may be rigidified while preserving its permeability to liquids. The paper (in this instance cellulose cotton) remains absorbent.

The filter element furthermore may be fitted at its outside surface with polarizing positioning means which are small salient or hollow devices to position the filter element in a manner that it assumes a defined position within the case. These polarizing positioning means also may be notches, grooves or studs. They are configured on one or several surfaces of the filter element and preferably are situated on the cylindrical outside surfaces.

One application of a filter element of the invention concerns micro-filtration of oil of an automotive internal combustion engine in order to trap the microparticles which

are a predominant source of engine generated pollution. Illustratively, applicant has made in particular three different kinds of filter elements of different sizes for such an application. The approximate dimensions of these three kinds of filter elements are shown in the Table below.

Outside Diameter (mm)	Inside Diameter (mm)	Inside Surface (cm ²)	Axial Length (m)	Strip Length (m)	Weight (g)
72	28	135	152	47	139
84	35	230	210	62.5	256
84	35	300	273	62.5	332

In this case, the paper material is a strip of a single ply of cellulose cotton with a specific surface weight of 20 g/m².

This embodiment of the invention uses cellulose cotton, however other types of paper materials may be considered, for example products of paper fibers linked by latex or hot melting fibers when using a dry method.

Be it borne in mind that cellulose cotton offers moisture resistance because its manufacture includes a moisture-resistant agent.

Again, a strip of paper including several identical or different plies may be used, and sheets of other specific surface weights may be used as a function of the fluid being filtered, or as a function of flow or of the desired filtration.

Moreover, the filter element is not mandatorily in the form of a winding resulting from a single and continuous sheet of absorbent paper. The filter element also may be built using a series of sheets of absorbent paper which are configured in the manner of the disclosure of the document WO 96/05133. This document describes a manufacturing process for a paper roll involving interlacing sheets of paper.

Paper rolls including sheets which are superposed and/or combined, for example by bonding, embossing and/or knurling also are applicable.

The manufacture of such papers may incorporate agents which are resistant to the fluids being filtered in order to enhance sheet strength during filtration.

Additives also may be used as a function of filtration purposes such as cleansing, bactericidal action or enrichment of the filtered and recovered fluid, by incorporating a dehydrating agent, food supplements (in the case of filtering food oils), etc.

One or more components directly or indirectly affecting the properties of the filtered fluid also may be applied to or fixated on at least the surface of the filter element's inside wall.

It is understood furthermore that a filter element of the present invention may be used to filter any generic oil and even any kind of fluid (gases included). Such applications

PCT/FR99/01904

relate, for example to engine oils, hydraulic oils, cooking oils, etc.

CLAIMS

1. A filter element to filter a fluid, wherein the filter element (14) is used in a filter system (10) comprising a cylindrical case (12), said element (14) including an absorbent paper material in the form of a sheet and said element is configured to constitute a tubular cylinder inside said case (12) in a manner to partition an outer radial part (26) from an inner radial part (30), the fluid moving across the filter element (14) in a generally centripetal direction, characterized in that the filter element (14) is devoid of a central core.

2. Filter element as claimed in claim 1, characterized in that the mean inside diameter of the tubular cylinder is larger than $1/20^{\text{th}}$ of its mean outside diameter.

3. Filter element as claimed in claim 2, characterized in that the mean inside diameter of the tubular cylinder is greater than $1/4^{\text{th}}$ its mean outside diameter.

4. Filter element as claimed in claim 3, characterized in that the mean inside diameter of the tubular cylinder is between $1/3$ and $1/2$ its mean outside diameter.

5. Filter element as claimed in any of the above claims, characterized in that the mean inside diameter of the tubular cylinder is greater than 25 mm.

6. Filter element as claimed in any of the above claims, characterized in that the inside wall of the tubular cylinder exhibits a conical or cylindrical shape and a circular, polygonal or other cross-sectional shape.

7. Filter element as claimed in any of the above claims, characterized in that the filter element is fitted on its surface with at least one polarizing positioning means.

8. Filter element as claimed in any of the above claims, characterized in that the filter element (14) has a strip of absorbent paper material in the form of a continuous single sheet wound into a tubular cylinder.

9. Filter element as claimed in any of claims 1 through 7, characterized in that the filter element (14) includes a series of sheets of absorbent paper material which are interlaced to constitute a tubular cylinder.

10. Filter element as claimed in any of the above claims, characterized in that the sheet comprises several plies.

11. Filter element as claimed in any of the above claims, characterized in that the absorbent paper material is cellulose cotton.

12. Filter element as claimed in any of the above claims, characterized in that it is used in a fluid filtering system (10) for filtering oil of an automotive engine for example.

ABSTRACT

The invention relates to a filter element (14) for filtering a fluid and is used in a filtration system (10) including a cylindrical case (12), the filter element having an absorbent paper material in the form of a sheet and configured into a tubular cylinder inside the case (12) in a manner to partition a radially outside part (26) from a radially inside part (30), the fluid moving across the filter element (14) in a generally centripetal direction, the filter element (14) being characterized in that it is devoid of a central core.




FIG. 2

COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION

Docket No. 5418

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled FILTERING ELEMENT MADE OF ABSORBENT PAPER MATERIAL IN

THE FORM OF A TUBULAR CYLINDER

the specification of which is attached hereto unless the following box is checked:

[X] was filed on August 2, 1999 as United States Application Number or PCT International Application Number PCT/FR99/01904 and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Claimed

<u>98 09986</u> (Number)	<u>France</u> (Country)	<u>4 August 1998</u> (Day/Month/Year Filed)	Yes [X] No []
<u>PCT/FR99/01904</u> (Number)	<u>PCT</u> (Country)	<u>2 August 1999</u> (Day/Month/Year Filed)	Yes [X] No []

I hereby claim the benefit under 35 U.S.C. §119(e) of any United States provisional application(s) listed below.

(Application Number)

(Filing Date)

(Application Number)

(Filing Date)

I hereby claim the benefit under 35 U.S.C. §120 of any United States application(s), or §365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. §112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

(Application No.)

(Filing Date)

(Status-patented, pending, abandoned)

(Application No.)

(Filing Date)

(Status-patented, pending, abandoned)

I (we) hereby appoint the following attorney with full power of substitution to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

ALFRED W. BREINER, Reg. No. 18,676; THEODORE A. BREINER, Reg. No. 32,103; and MARY J. BREINER, Reg. No. 33,161.

Address all correspondence to -

BREINER & BREINER, 115 North Henry Street
P.O. Box 19290, Alexandria, Virginia 22320-0290

Address all telephone calls to -

Mary J. Breiner at (703) 684-6885

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor:

(given name, family name) Yves MALECOT

Inventor's Signature [Signature]

Date 24/01/2001

Residence: Crosville la Vieille, France Citizenship: French ✓

Post Office Address: 46, rue du Val Saint-Martin

F-27110 Crosville la Vieille, France

Full Name of Second Joint Inventor, if any

(given name, family name) Joel HUNGLER

Inventor's Signature [Signature]

Date 25/01/2001

Residence: Ailly, France FRX Citizenship: French ✓

Post Office Address: 15, rue des Long Champs, Ingremare

F-27600 Ailly, France

Full Name of Third Joint Inventor, if any

(given name, family name) _____

Inventor's Signature _____

Date _____

Residence: _____ Citizenship: _____

Post Office Address: _____